



SIM7500_SIM7600_SIM7800 Series_SSL_AT Command Manual_V1.00

LTE Module

Shanghai SIMCom Wireless Solutions Ltd.
Building A, SIM Technology Building, No.633, Jinzhong Road
Changning District 200335
Tel:86-21-31575100/31575200
support@simcom.com
www.simcom.com

Document Title:	SIM7500_SIM7600_SIM7800 Series_SSL_AT Command Manual
Version:	1.00
Date:	2018-10-12
Status:	Release
Document ID:	SIM7500_SIM7600_SIM7800 Series_SSL_AT Command Manual_V1.00

General Notes

SIMCom offers this information as a service to its customers, to support application and engineering efforts that use the products designed by SIMCom. The information provided is based upon requirements specifically provided to SIMCom by the customers. SIMCom has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by SIMCom within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

Copyright

This document contains proprietary technical information which is the property of SIMCom Limited., copying of this document and giving it to others and the using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights reserved in the event of grant of a patent or the registration of a utility model or design. All specification supplied herein are subject to change without notice at any time.

Copyright © Shanghai SIMCom Wireless Solutions Ltd. 2018

Version History

Version	Date	Chapter	What is new
V1.00	2018-09-28		New version

SIMCom Confidential

Contents

Version History	2
Contents.....	3
1 Introduction.....	4
1.1 The SSL Context Management AT Commands	4
1.2 The process of Using SSL AT Commands.....	4
2 Description of AT Command	5
2.1 SSL Context Management AT	5
2.1.1 AT+CSSLCFG Configure the SSL Context.....	5
2.1.2 AT+CCERTDOWN Download certificate into the module	9
2.1.3 AT+CCERTLIST List certificates.....	9
2.1.4 AT+CCERTDELETE Delete certificates.....	10
2.2 SSL Services AT	10
2.2.1 AT+CCHSET Configure the report mode of sending and receiving data.....	10
2.2.2 AT+CCHMODE Configure the mode of sending and receiving data.....	11
2.2.3 AT+CCHSTART Start SSL service.....	12
2.2.4 AT+CCHSTOP Stop SSL service	13
2.2.5 AT+CCHADDR Get the IPv4 address.....	13
2.2.6 AT+CCHSSLCFG Set the SSL context	13
2.2.7 AT+CCHOPEN Connect to server.....	14
2.2.8 AT+CCHCLOSE Disconnect from server	15
2.2.9 AT+CCHSEND Send data to server	16
2.2.10 AT+CCHRECV Read the cached data that received from the server	17
2.3 Command result codes and unsolicited codes	18
2.3.1 Command result <err> codes.....	18
2.3.2 Unsolicited result codes	19
3 Example.....	19
3.1 Access to TCP server	20
3.2 Access to SSL/TLS server (not verify server and client).....	22
3.3 Access to SSL/TLS server (only verify the server)	24
3.4 Access to SSL/TLS server (verify server and client).....	26
3.5 Access to SSL/TLS server (only verify the client)	28
3.6 Access to SSL/TLS server in transparent mode.....	31
3.7 Download certificate into module.....	32

This document is a reference guide to all the AT commands defined for SSL. Through these SSL AT commands, you can communicate with a TCP or SSL server.

1 Introduction

1.1 The SSL Context Management AT Commands

Step 1: Configure SSL version by AT+CSSLCFG=“sslversion”,<ssl_ctx_index>,<sslversion>.

Step 2: Configure SSL authentication mode by AT+CSSLCFG=“authmode”,<ssl_ctx_index>,<authmode>.

Step 3: Configure the flag of ignore local time by

AT+CSSLCFG=“ignorlocaltime”,<ssl_ctx_index>,<ignoretime>.

Step 4: Configure the max time in SSL negotiation stage by

AT+CSSLCFG=“negotiatetime”,<ssl_ctx_index>,<negotiatetime>.

Step 5: Configure the server root CA by AT+CSSLCFG=“cacert”,<ssl_ctx_index>,<ca_file>.

Step 6: Configure the client certificate by AT+CSSLCFG=“clientcert”,<ssl_ctx_index>,<clientcert_file>.

Step 7: Configure the client key by AT+CSSLCFG=“clientkey”,<ssl_ctx_index>,<clientkey_file>.

Step 8: Download the certificate into the module by AT+CCERTDOWN.

Step 9: Delete the certificate from the module by AT+CCERTDELETE.

Step 10: List the certificates by AT+CCERTLIST.

1.2 The process of Using SSL AT Commands

Step 1: Ensure GPRS network is available before performing SSL related operations.

Step 2: Configure the parameter of PDP context by AT+CGDCONT.

Step 3: Activate the PDP context to start SSL service by AT+CCHSTART.

Step 4: Configure SSL context by AT+CSSLCFG (if connect to SSL/TLS server).

Step 5: Set the SSL context used in SSL connection by AT+CCHSSLCFG (if connect to SSL/TLS server).

Step 6: Connect to the server by AT+CCHOPEN.

Step 7: Send data to the server by AT+CCHSEND.

Step 8: Receive data from server by AT+CCHRECV in manual receive mode.

Step 9: Disconnect from the server by AT+CCHCLOSE.

Step 10: Deactivate the PDP context to stop SSL service by AT+CCHSTOP.

Note:

2 Description of AT Command

2.1 SSL Context Management AT

2.1.1 AT+CSSLCFG Configure the SSL Context

AT+CSSLCFG Configure the SSL Context	
<p>Test Command AT+CSSLCFG=?</p>	<p>Response</p> <pre>+CSSLCFG: "sslversion",(0-9),(0-4) +CSSLCFG: "authmode",(0-9),(0-3) +CSSLCFG: "ignorelocaltime",(0-9),(0,1) +CSSLCFG: "negotiatetime",(0-9),(10-300) +CSSLCFG: "cacert",(0-9),(5-128) +CSSLCFG: "clientcert",(0-9),(5-128) +CSSLCFG: "clientkey",(0-9),(5-128)</pre> <p>OK</p>
<p>Read Command AT+CSSLCFG?</p>	<p>Response</p> <pre>+CSSLCFG: 0,<sslversion>,<authmode>,<ignoreftime>,<negotiatetime>,< ca_file>,<clientcert_file>,<clientkey_file> +CSSLCFG: 1,<sslversion>,<authmode>,<ignoreftime>,<negotiatetime>,< ca_file>,<clientcert_file>,<clientkey_file> +CSSLCFG: 2,<sslversion>,<authmode>,<ignoreftime>,<negotiatetime>,< ca_file>,<clientcert_file>,<clientkey_file> +CSSLCFG: 3,<sslversion>,<authmode>,<ignoreftime>,<negotiatetime>,< ca_file>,<clientcert_file>,<clientkey_file> +CSSLCFG: 4,<sslversion>,<authmode>,<ignoreftime>,<negotiatetime>,< ca_file>,<clientcert_file>,<clientkey_file> +CSSLCFG: 5,<sslversion>,<authmode>,<ignoreftime>,<negotiatetime>,< ca_file>,<clientcert_file>,<clientkey_file></pre>

	<p>+CSSLCFG: 6,<sslversion>,<authmode>,<ignoreltime>,<negotiatetime>,<ca_file>,<clientcert_file>,<clientkey_file></p> <p>+CSSLCFG: 7,<sslversion>,<authmode>,<ignoreltime>,<negotiatetime>,<ca_file>,<clientcert_file>,<clientkey_file></p> <p>+CSSLCFG: 8,<sslversion>,<authmode>,<ignoreltime>,<negotiatetime>,<ca_file>,<clientcert_file>,<clientkey_file></p> <p>+CSSLCFG: 9,<sslversion>,<authmode>,<ignoreltime>,<negotiatetime>,<ca_file>,<clientcert_file>,<clientkey_file></p> <p>OK</p>
Write Command <pre>/*Query the configuration of the specified SSL context*/ AT+CSSLCFG=<ssl_ctx_index></pre>	<p>Response</p> <p>+CSSLCFG: <ssl_ctxindex>,<sslversion>,<authmode>,<ignoreltime>,<ne gotiatetime>,<ca_file>,<clientcert_file>,<clientkey_file></p> <p>OK</p>
Write Command <pre>/*Configure the version of the specified SSL context*/ AT+CSSLCFG="sslversion",<ssl_ctx_in dex>,<sslversion></pre>	<p>Response</p> <p>a)If successfully: OK</p> <p>b)If failed: ERROR</p>
Write Command <pre>/*Configure the authentication mode of the specified SSL context*/ AT+CSSLCFG="authmode",<ssl_ctx_in dex>,<authmode></pre>	<p>Response</p> <p>a)If successfully: OK</p> <p>b)If failed: ERROR</p>
Write Command <pre>/*Configure the ignore local time flag of the specified SSL context*/ AT+CSSLCFG="ignorelocaltime",<ssl_c tx_index>,<ignoreltime></pre>	<p>Response</p> <p>a)If successfully: OK</p> <p>b)If failed: ERROR</p>
Write Command <pre>/*Configure the negotiate timeout value of the specified SSL context*/ AT+CSSLCFG="negotiatetime",<ssl_ctx</pre>	<p>Response</p> <p>a)If successfully: OK</p> <p>b)If failed:</p>

_index>,<negotiatetime>	ERROR
Write Command <i>/*Configure the server root CA of the specified SSL context*/</i> AT+CSSLCFG="cacert",<ssl_ctx_index>,<ca_file>	Response a)If successfully: OK b)If failed: ERROR
Write Command <i>/*Configure the client certificate of the specified SSL context*/</i> AT+CSSLCFG="clientcert",<ssl_ctx_index>,<clientcert_file>	Response a)If successfully: OK b)If failed: ERROR
Write Command <i>/*Configure the client key of the specified SSL context*/</i> AT+CSSLCFG="clientkey",<ssl_ctx_index>,<clientkey_file>	Response a)If successfully: OK b)If failed: ERROR

Defined Values

<ssl_ctx_index>	The SSL context ID. The range is 0-9.
<sslversion>	The SSL version, the default value is 4. 0 – SSL3.0 1 – TLS1.0 2 – TLS1.1 3 – TLS1.2 4 – All The configured version should be support by server. So you should use the default value if you can't confirm the version which the server supported.
<authmode>	The authentication mode, the default value is 0. 0 – no authentication. 1 –server authentication. It needs the root CA of the server. 2 –server and client authentication. It needs the root CA of the server, the cert and key of the client. 3–client authentication and no server authentication. It needs the cert and key of the client.
<ignorelttime>	The flag to indicate how to deal with expired certificate, the default value is 1. 0 – care about time check for certification. 1 – ignore time check for certification When set the value to 0, it need to set the right current date and time by AT+CCLK when need SSL certification.

<negotiatetime>	The timeout value used in SSL negotiate stage. The range is 10-300 seconds. The default value is 300.
<ca_file>	<p>The root CA file name of SSL context. The file name must have type like “.pem” or “.der”. The length of filename is from 5 to 128 bytes.</p> <p>If the filename contains non-ASCII characters, the file path parameter should contain a prefix of {non-ascii} and the quotation mark (The string in the quotation mark should be hexadecimal of the filename’s UTF8 code).</p> <p>There are two ways to download certificate files to module:</p> <ol style="list-style-type: none"> 1. By AT+CCERTDOWN. 2. By FTPS or HTTPS commands. Please refer to: SIM7500_SIM7600_SIM7800 Series_FTPS_AT Command Manual and SIM7500_SIM7600_SIM7800 Series_HTTP_AT Command Manual
<clientcert_file>	<p>The client cert file name of SSL context. The file name must have type like “.pem” or “.der”. The length of filename is from 5 to 128 bytes.</p> <p>If the filename contains non-ASCII characters, the file path parameter should contain a prefix of {non-ascii} and the quotation mark (The string in the quotation mark should be hexadecimal of the filename’s UTF8 code).</p> <p>There are two ways to download certificate files to module:</p> <ol style="list-style-type: none"> 1. By AT+CCERTDOWN. 2. By FTPS or HTTPS commands. Please refer to: SIM7500_SIM7600_SIM7800 Series_FTPS_AT Command Manual and SIM7500_SIM7600_SIM7800 Series_HTTP_AT Command Manual
<clientkey_file>	<p>The client key file name of SSL context. The file name must have type like “.pem” or “.der”. The length of filename is from 5 to 128 bytes.</p> <p>If the filename contains non-ASCII characters, the file path parameter should contain a prefix of {non-ascii} and the quotation mark (The string in the quotation mark should be hexadecimal of the filename’s UTF8 code).</p> <p>There are two ways to download certificate files to module:</p> <ol style="list-style-type: none"> 1. By AT+CCERTDOWN. 2. By FTPS or HTTPS commands. Please refer to: SIM7500_SIM7600_SIM7800 Series_FTPS_AT Command Manual and SIM7500_SIM7600_SIM7800 Series_HTTP_AT

Command Manual

2.1.2 AT+CCERTDOWN Download certificate into the module

AT+CCERTDOWN Download certificate into the module	
Test Command AT+CCERTDOWN=?	Response +CCERTDOWN: (5-128),(1-10240) OK
Write Command AT+CCERTDOWN=<filename>,<len>	Response a) If it can be download: > <input data here> b) If failed: ERROR

Defined Values

<filename>	The name of the certificate/key file. The file name must have type like “.pem” or “.der”. The length of filename is from 5 to 128 bytes. If the filename contains non-ASCII characters, the file path parameter should contain a prefix of {non-ascii} and the quotation mark (The string in the quotation mark should be hexadecimal of the filename’s UTF8 code). For example: If you want to download a file with name “中华.pem”, you should convert the “中华.pem” to UTF8 coding (中华.pem), then input the hexadecimal (262378344532443B262378353334453B2E70656D) of UTF8 coding.
<len>	The length of the file data to send. The range is from 1 to 10240 bytes.

2.1.3 AT+CCERTLIST List certificates

AT+CCERTLIST List certificates	
Execute Command AT+CCERTLIST	Response [+CCERTLIST:<file_name> [+CCERTLIST:<file_name>] ...

	<CR><LF>] OK
--	---

Defined Values

<filename>	The certificate/key files which has been downloaded to the module. If the filename contains non-ASCII characters, it will show the non-ASCII characters as UTF8 code.
-------------------------	--

2.1.4 AT+CCERTDELETE Delete certificates

AT+CCERTDELETE Delete certificate from the module

Write Command AT+CCERTDELETE=<filename>	Response a) If delete successfully: OK b) If failed: ERROR
---	--

Defined Values

<filename>	The name of the certificate/key file. The file name must have type like “.pem” or “.der”. The length of filename is from 5 to 128 bytes. If the filename contains non-ASCII characters, the file path parameter should contain a prefix of {non-ascii} and the quotation mark (The string in the quotation mark should be hexadecimal of the filename’s UTF8 code). For example: If you want to download a file with name “中华.pem”, you should convert the “中华.pem” to UTF8 coding (&x4E2D;&x534E;.pem), then input the hexadecimal (262378344532443B262378353334453B2E70656D) of UTF8 coding.
-------------------------	--

2.2 SSL Services AT

2.2.1 AT+CCHSET Configure the report mode of sending and receiving data

AT+CCHSET is used to configure the mode of sending and receiving data. It must be called before AT+CCHSTART.

AT+CCHSET Configure the report mode of sending and receiving

Test Command	Response +CCHSET: (0,1),(0,1)
AT+CCHSET=?	OK
Read Command	Response +CCHSET: <report_send_result>,<recv_mode>
AT+CCHSET?	OK
Write Command	Response a) If successfully: OK b) If failed: ERROR
AT+CCHSET=<report_send_result>[,<recv_mode>]	

Defined Values

<report_send_result>	Whether to report result of CCHSEND, the default value is 0: <u>0</u> – No. 1 – Yes. Module will report +CCHSEND: <session_id>,<err> to MCU when complete sending data.
<recv_mode>	The receiving mode: <u>0</u> – Output the data to MCU whenever received data. 1 – Module caches the received data and notifies MCU with +CCHEVENT: <session_id>, RECV EVENT. MCU can use AT+CCHRECV to receive the cached data (only in manual receiving mode).

2.2.2 AT+CCHMODE Configure the mode of sending and receiving data

AT+CCHMODE is used to elect transparent mode (data mode) or non-transparent mode (command mode). The default mode is non-transparent mode. This AT command must be called before calling AT+CCHSTART.

NOTE: There is only one session in the transparent mode, it's the first session.

AT+CCHMODE Configure the mode of sending and receiving

Test Command	Response +CCHMODE: (0,1)
AT+CCHMODE=?	OK
Read Command	Response +CCHMODE: <mode>
AT+CCHMODE?	

	OK
Write Command AT+CCHMODE=<mode>	Response a)If successfully: OK b)If failed: ERROR

Defined Values

<mode>	The mode value: 0 – Normal. 1 – Transparent mode The default value is 0.
---------------------	---

2.2.3 AT+CCHSTART Start SSL service

AT+CCHSTART is used to start SSL service by activating PDP context. You must execute AT+CCHSTART before any other SSL related operations.

AT+CCHSTART Start SSL service	
Execute Command AT+CCHSTART	Response a)If start SSL service successfully: OK +CCHSTART: 0 b)If start SSL service successfully: +CCHSTART: 0 OK c)If failed: ERROR d)If failed: ERROR
Maximum Response Time	120000ms

Defined Values

<err>	The result code, please refer to chapter 2.3.1
--------------------	--

2.2.4 AT+CCHSTOP Stop SSL service

AT+CCHSTOP is used to stop SSL service.

AT+CCHSTOP STOP SSL service	
Execute Command AT+CCHSTOP	<p>Response</p> <p>a)If stop SSL service successfully: +CCHSTOP: 0</p> <p>OK</p> <p>b)If stop SSL service successfully: OK</p> <p>+CCHSTOP: 0</p> <p>c)If failed: ERROR</p>

Defined Values

<err>	The result code, please refer to chapter 2.3.1
--------------------	--

2.2.5 AT+CCHADDR Get the IPv4 address

AT+CCHADDR is used to get the IPv4 address after calling AT+CCHSTART.

AT+CCHSADDR Get the IPv4 address	
Execute Command AT+CCHADDR	<p>Response</p> <p>+CCHADDR: <ip_address></p> <p>OK</p>

Defined Values

<ip_address>	A string parameter that identifies the IPv4 address after PDP activated.
---------------------------	--

2.2.6 AT+CCHSSLCFG Set the SSL context

AT+CCHSSLCFG is used to set the SSL context which to be used in the SSL connection. It must be called before AT+CCHOPEN and after AT+CCHSTART. The setting will be cleared after the CCHOPEN operation is finished.

NOTE: If you don't set the SSL context by this command before connecting to SSL/TLS server by AT+CCHOPEN, the CCHOPEN operation will use the SSL context as same as index <session_id> (the 1st parameter of AT+CCHOPEN) when connecting to the server.

AT+CCHSSLCFG Set the SSL context	
Test Command AT+CCHSSLCFG=?	Response +CCHSSLCFG: (0,1),(0-9) OK
Read Command AT+CCHSSLCFG?	Response +CCHSSLCFG: <session_id>,[<ssl_ctx_index>] +CCHSSLCFG: <session_id>,[<ssl_ctx_index>] OK
Write Command AT+CCHSSLCFG=<session_id>,<ssl_ctx_index>	Response a)If successfully: OK b)If failed: ERROR

Defined Values

<session_id>	The session_id to operate. It's from 0 to 1.
<ssl_ctx_index>	The SSL context ID which will be used in the SSL connection. Refer to the <ssl_ctx_index> of AT+CSSLCFG.

2.2.7 AT+CCHOPEN Connect to server

AT+CCHOPEN is used to connect to the server.

NOTE: If you don't set the SSL context by AT+CCHSSLCFG before connecting a SSL/TLS server by AT+CCHOPEN, it will use the <session_id> (the 1'st parameter of AT+CCHOPEN) SSL context when connecting to the server.

AT+CCHOPEN Connect to server	
Test Command AT+CCHOPEN=?	Response +CCHOPEN: (0,1),"ADDRESS", (1-65535)[,(1-2)[,(1-65535)]] OK
Write Command AT+CCHOPEN=<session_id>, "<host>", <port>[<client_type>,[<bind_port>]]	Response a)If connect successfully: +CCHOPEN: <session_id>,0

<p>OK</p> <p>b) If connect successfully:</p> <p>OK</p> <p>+CCHOPEN: <session_id>,0</p> <p>c) If connect successfully in transparent mode:</p> <p>CONNECT [<text>]</p> <p>d) If failed:</p> <p>OK</p> <p>+CCHOPEN: <session_id>,<err></p> <p>e) If failed:</p> <p>ERROR</p> <p>f) If failed in transparent mode:</p> <p>CONNECT FAIL</p>

Defined Values

<session_id>	The session index to operate. It's from 0 to 1.
<host>	The server address, maximum length is 256 bytes.
<port>	The server port which to be connected, the range is from 1 to 65535.
<client_type>	The type of client: 1 – TCP client. 2 – SSL/TLS client.
<bind_port>	The local port for channel, the range is from 1 to 65535.
<text>	CONNECT result code string; the string formats please refer ATX/AT\V/AT&E command.
<err>	The result code: 0 is success. Other values are failure. Please refer to chapter 2.3.1

2.2.8 AT+CCHCLOSE Disconnect from server

AT+CCHCLOSE is used to disconnect from the server.

AT+CCHCLOSE Disconnect from the Server	
Write Command AT+CCHCLOSE=<session_id>	<p>Response</p> <p>a) If successfully:</p> <p>+CCHCLOSE: <session_id>,0</p> <p>OK</p>

	<p>b) If successfully: OK</p> <p>+CCHCLOSE: <session_id>,0</p> <p>c) If successfully in transparent mode: OK</p> <p>CLOSED</p> <p>d) If failed: ERROR</p>
--	---

Defined Values

<session_id>	The session index to operate. It's from 0 to 1.
<err>	The result code: 0 is success. Other values are failure. Please refer to chapter 2.3.1.

2.2.9 AT+CCHSEND Send data to server

You can use AT+CCHSEND to send data to server.

AT+CCHSEND Send Data	
Test Command AT+CCHSEND=?	<p>Response:</p> <p>+CCHSEND: (0,1),(1-2048)</p> <p>OK</p>
Read Command AT+CCHSEND?	<p>Response:</p> <p>+CCHSEND: 0,<unsent_len_0>,1,<unsent_len_1></p> <p>OK</p>
Write Command AT+CCHSEND=<session_id>,<len>	<p>Response</p> <p>a) if parameter is right:</p> <p>></p> <p><input data here></p> <p>When the total size of the inputted data reaches <len>, TA will report the following code. Otherwise, the serial port will be</p>

blocked.

OK

b) If parameter is wrong or other errors occur:

ERROR

Defined Values

<code><session_id></code>	The session_id to operate. It's from 0 to 1.
<code><len></code>	The length of data to send. Its range is from 1 to 2048 bytes.
<code><unsent_len_0></code>	The data of connection 0 cached in sending buffer which is waiting to be sent.
<code><unsent_len_1></code>	The data of connection 1 cached in sending buffer which is waiting to be sent.

2.2.10 AT+CCHRECV Read the cached data that received from the server

You can use AT+CCHRECV to read the cached data which received from the server.

AT+CCHRECV Receive the cached data that received from server	
Read Command AT+CCHRECV?	<p>Response +CCHRECV: LEN,<cache_len_0>,<cache_len_1></p> <p>OK</p>
Write Command AT+CCHRECV=<session_id>[,<max_recv_len>]	<p>Response a) if parameter is right and there are cached data: OK</p> <p>[+CCHRECV: DATA, <session_id>,<len> ... +CCHRECV: DATA, <session_id>,<len> ...] +CCHRECV: <session_id>,<err></p> <p>b) if parameter is not right or any other error occurs: +CCHRECV: <session_id>,<err></p> <p>ERROR</p>

Defined Values

<code><session_id></code>	The session_id to operate. It's from 0 to 1.
<code><max_recv_len></code>	Maximum bytes of data to receive in the current AT+CCHRECV

	<p>calling. It will read all the received data when the value is greater than the length of RX data cached for session <session_id>. 0 means the maximum bytes to receive is 2048 bytes. (But, when 2048 is greater than the length of RX data cached for session <session_id>, 0 means the length of RX data cached for session <session_id>). The default value is the length of RX data cached for session <session_id>. It will be not allowed when there is no data in the cache.</p>
<cache_len_0>	The length of RX data cached for connection 0.
<cache_len_1>	The length of RX data cached for connection 1.
<len>	The length of data followed.
<err>	The result code: 0 is success. Other values are failure. Please refer to chapter 2.3.1.

2.3 Command result codes and unsolicited codes

2.3.1 Command result <err> codes

Result codes	
0	Operation succeeded
1	Alerting state(reserved)
2	Unknown error
3	Busy
4	Peer closed
5	Operation timeout
6	Transfer failed
7	Memory error
8	Invalid parameter
9	Network error
10	Open session error
11	State error
12	Create socket error
13	Get DNS error
14	Connect socket error
15	Handshake error
16	Close socket error
17	Nonet
18	Send data timeout

19	Not set certificates
----	----------------------

2.3.2 Unsolicited result codes

Unsolicited codes	
+CCHEVENT: <session_id>,RECV EVENT	In manual receiving mode, when new data of a connection arriving to the module, this unsolicited result code will be reported to MCU.
+CCH_RECV_CLOSED: <session_id>,<err>	When receive data occurred any error, this unsolicited result code will be reported to MCU.
+CCH_PEER_CLOSED: <session_id>	The connection is closed by the server.

3 Example

Before all SSL related operations, we should ensure the following:

- a) ensure GPRS network is available:

AT+CSQ

+CSQ: 23,0

OK

AT+CREG?

+CREG: 0,1

OK

AT+CGREG?

+CGREG: 0,1

OK

- b) PDP context Enable:

```
// Specify the parameter value of the PDP context corresponding to cid
```

```
AT+CGSOCKCONT=1,"IP","CMNET"
```

OK

```
AT+CGPADDR
```

```
+CGPADDR: 1,10.49.14.68 //ensure the first PDP context get a IP address
```

```
+CGPADDR: 4.0.0.0.0
```

OK

Note: usually CSOCKAUTH and CSOCKSETPN parameter are kept default if not care about.

3.1 Access to TCP server

Following commands shows how to communicate with a TCP server.

```
// Enable reporting +CHSEND result
```

```
AT+CCHSET=1
```

OK

```
//start SSL service, activate PDP context
```

```
AT+CCHSTART
```

OK

```
+CCHSTART: 0
```

```
//connect to TCP server
```

```
AT+CCHOPEN=0,www.baidu.com,80,1
```

OK

```
+CCHOPEN: 0,0
```

```
//send data to server
```

```
AT+CCHSEND=0,121
```

```
>GET / HTTP/1.1
```

```
Host: www.baidu.com
```

```
User-Agent: Mozilla/5.0 (Windows NT 5.1; rv:2.0) Gecko/20100101 Firefox/4.0
```

Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: zh-cn,zh;q=0.5
Accept-Encoding: gzip, deflate
Accept-Charset: GB2312,utf-8;q=0.7,*;q=0.7
Keep-Alive: 115
Connection: keep-alive
Cookie: BAIDUID=D6F6D0D297CCAE39BD45C683996696C7:FG=1;
Hm_lvt_9f14aaa038bbba8b12ec2a4a3e51d254=1321597443439;
USERID=e194072f4759c0f7c2b6e5d3b09298984fd1

OK

+CCHSEND: 0,0
//report the received data from server
+CCHRECV: DATA,0,757
HTTP/1.1 302 Found
Connection: Keep-Alive
Content-Length: 225
Content-Type: text/html
Date: Wed, 05 Sep 2018 08:59:38 GMT
Location: https://www.baidu.com/
Server: BWS/1.1
Set-Cookie: BIDUPSID=D6F6D0D297CCAE39BD45C683996696C7; expires=Thu, 31-Dec-37 23:55:55
GMT; max-age=2147483647; path=/; domain=.baidu.com
Set-Cookie: PSTM=1536137978; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/;
domain=.baidu.com
Set-Cookie: BD_LAST_QID=11878059346481009304; path=/; Max-Age=1
X-Ua-Compatible: IE=Edge,chrome=1

<html>
<head><title>302 Found</title></head>
<body bgcolor="white">
<center><h1>302 Found</h1></center>
<hr><center>7a367f7b87705e16b985e34ca59b8ae8b1d28d47
Time : Tue Aug 21 10:55:16 CST 2018</center>

</body>

</html>

//Disconnect from the Service

AT+CCHCLOSE=0

OK

+CCHCLOSE: 0

//stop SSL Service

AT+CCHSTOP

OK

+CCHSTOP: 0

3.2 Access to SSL/TLS server (not verify server and client)

Following commands shows how to access to a SSL/TLS server without verifying the server. It needs to configure the authentication mode to 0, and then it will connect to the server successfully.

// Set the SSL version of the first SSL context

AT+CSSLCFG="sslversion",0,4

OK

// Set the authentication mode(not verify server) of the first SSL context

AT+CSSLCFG="authmode",0,0

OK

// Enable reporting +CHSEND result

AT+CCHSET=1

OK

// start SSL service, activate PDP context

AT+CCHSTART

OK

+CCHSTART: 0

// Set the first SSL context to be used in the SSL connection

AT+CCHSSLCFG=0,0

OK

//connect to SSL/TLS server

AT+CCHOPEN=0,"www.baidu.com", 443,2

OK

+CCHOPEN: 0,0

//send data to server

AT+CCHSEND=0,121

>GET / HTTP/1.1

Host: www.baidu.com

User-Agent: MAUI htp User Agent

Proxy-Connection: keep-alive

Content-Length: 0

OK

+CCHSEND: 0,0

//report the received data from server

+CCHRECV: DATA,0,917

HTTP/1.1 200 OK

Accept-Ranges: bytes

Cache-Control: no-cache

Connection: Keep-Alive

Content-Length: 227

Content-Type: text/html

Date: Tue, 04 Sep 2018 06:21:35 GMT

Etag: "5b7b7f40-e3"

Last-Modified: Tue, 21 Aug 2018 02:56:00 GMT

P3p: CP=" OTI DSP COR IVA OUR IND COM "

Pragma: no-cache

Server: BWS/1.1

Set-Cookie: BD_NOT_HTTPS=1; path=/; Max-Age=300

Set-Cookie: BIDUPSID=D95046B2B3D5455BF01A622DB8DED9EA; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com

Set-Cookie: PSTM=1536042095; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com

Strict-Transport-Security: max-age=0

X-Ua-Compatible: IE=Edge,chrome=1

<html>

<head>

<script>

location.replace(location.href.replace("https://","http://"));

</script>

</head>

<body>

<noscript><meta http-equiv="refresh" content="0;url=http://www.baidu.com/"></noscript>

</body>

</html>

//Disconnect from the Service

AT+CCHCLOSE=0

OK

```
+CCHCLOSE: 0  
//stop SSL Service  
AT+CCHSTOP  
OK
```

```
+CCHSTOP: 0
```

3.3 Access to SSL/TLS server (only verify the server)

Following commands shows how to access to a SSL/TLS server with verifying the server. It needs to configure the authentication mode to 1 and the right server root CA, and then it will connect to the server successfully.

```
// Set the SSL version of the first SSL context  
AT+CSSLCFG="sslversion",0,4  
OK  
// Set the authentication mode(verify server) of the first SSL context  
AT+CSSLCFG="authmode",0,1  
OK  
// Set the server root CA of the first SSL context  
AT+CSSLCFG="cacert",0,"ca_cert.pem"  
OK  
// Enable reporting +CHSEND result  
AT+CCHSET=1  
OK  
// start SSL service, activate PDP context  
AT+CCHSTART  
OK  
+CCHSTART: 0  
// Set the first SSL context to be used in the SSL connection  
AT+CCHSSLCFG=0,0  
OK  
//connect to SSL/TLS server  
AT+CCHOPEN=0,"www.baidu.com",443,2  
OK
```

```
+CCHOPEN: 0,0
//send data to server
AT+CCHSEND=0,121
>GET / HTTP/1.1
Host: www.baidu.com
User-Agent: MAUI htp User Agent
Proxy-Connection: keep-alive
Content-Length: 0
```

OK

```
+CCHSEND: 0,0
//report the received data from server
+CCHRECV: DATA,0,917
HTTP/1.1 200 OK
Accept-Ranges: bytes
Cache-Control: no-cache
Connection: Keep-Alive
Content-Length: 227
Content-Type: text/html
Date: Tue, 04 Sep 2018 06:21:35 GMT
Etag: "5b7b7f40-e3"
Last-Modified: Tue, 21 Aug 2018 02:56:00 GMT
P3p: CP=" OTI DSP COR IVA OUR IND COM "
Pragma: no-cache
Server: BWS/1.1
Set-Cookie: BD_NOT_HTTPS=1; path=/; Max-Age=300
Set-Cookie: BIDUPSID=D95046B2B3D5455BF01A622DB8DED9EA; expires=Thu, 31-Dec-37 23:55:55
GMT; max-age=2147483647; path=/; domain=.baidu.com
Set-Cookie: PSTM=1536042095; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/;
domain=.baidu.com
Strict-Transport-Security: max-age=0
X-Ua-Compatible: IE=Edge,chrome=1
```

```
<html>
<head>
    <script>
        location.replace(location.href.replace("https://","http://"));
    </script>
</head>
<body>
    <noscript><meta http-equiv="refresh" content="0;url=http://www.baidu.com/"></noscript>
```

```
</body>
</html>
```

//Disconnect from the Service

AT+CCHCLOSE=0

OK

+CCHCLOSE: 0

//stop SSL Service

AT+CCHSTOP

OK

+CCHSTOP: 0

3.4 Access to SSL/TLS server (verify server and client)

Following commands shows how to access to a SSL/TLS server with verifying the server and client. It needs to configure the authentication mode to 2, the right server root CA, the right client certificate and key, and then it will connect to the server successfully.

```
// Set the SSL version of the first SSL context
```

AT+CSSLCFG="sslversion",0,4

OK

```
// Set the authentication mode(verify server and client) of the first SSL context
```

AT+CSSLCFG="authmode",0,2

OK

```
// Set the server root CA of the first SSL context
```

AT+CSSLCFG="cacert",0,"ca_cert.pem"

OK

```
// Set the client certificate of the first SSL context
```

AT+CSSLCFG="clientcert",0,"cert.pem"

OK

```
// Set the client key of the first SSL context
```

AT+CSSLCFG="clientkey",0,"key_cert.pem"

OK

// Enable reporting +CHSEND result

AT+CCHSET=1

OK

// start SSL service, activate PDP context

AT+CCHSTART

OK

+CCHSTART: 0

// Set the first SSL context to be used in the SSL connection

AT+CCHSSLCFG=0,0

OK

//connect to SSL/TLS server

AT+CCHOPEN=0, "www.baidu.com",443,2

OK

+CCHOPEN: 0,0

//send data to server

AT+CCHSEND=0,121

>GET / HTTP/1.1

Host: www.baidu.com

User-Agent: MAUI htp User Agent

Proxy-Connection: keep-alive

Content-Length: 0

OK

+CCHSEND: 0,0

//report the received data from server

+CCHRECV: DATA,0,917

HTTP/1.1 200 OK

Accept-Ranges: bytes

Cache-Control: no-cache

Connection: Keep-Alive

Content-Length: 227

Content-Type: text/html

Date: Tue, 04 Sep 2018 06:21:35 GMT

Etag: "5b7b7f40-e3"

Last-Modified: Tue, 21 Aug 2018 02:56:00 GMT

P3p: CP=" OTI DSP COR IVA OUR IND COM "

Pragma: no-cache

Server: BWS/1.1

Set-Cookie: BD_NOT_HTTPS=1; path=/; Max-Age=300
Set-Cookie: BIDUPSID=D95046B2B3D5455BF01A622DB8DED9EA; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com
Set-Cookie: PSTM=1536042095; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com
Strict-Transport-Security: max-age=0
X-UA-Compatible: IE=Edge,chrome=1

```
<html>
<head>
    <script>
        location.replace(location.href.replace("https://","http://"));
    </script>
</head>
<body>
    <noscript><meta http-equiv="refresh" content="0;url=http://www.baidu.com/"></noscript>
</body>
</html>
```

//Disconnect from the Service

AT+CCHCLOSE=0

OK

+CCHCLOSE: 0

//stop SSL Service

AT+CCHSTOP

OK

+CCHSTOP: 0

3.5 Access to SSL/TLS server (only verify the client)

Following commands shows how to access to a SSL/TLS server with verifying the client. It needs to configure the authentication mode to 3, the right client certificate and key, and then it will connect to the server successfully.

// Set the SSL version of the first SSL context

AT+CSSLCFG="sslversion",0,4

OK

// Set the authentication mode(only verify client) of the first SSL context

AT+CSSLCFG="authmode",0,3

OK

// Set the client certificate of the first SSL context

AT+CSSLCFG="clientcert",0,"cert.pem"

OK

// Set the client key of the first SSL context

AT+CSSLCFG="clientkey",0,"key_cert.pem"

OK

// Enable reporting +CHSEND result

AT+CCHSET=1

OK

// start SSL service, activate PDP context

AT+CCHSTART

OK

+CCHSTART: 0

// Set the first SSL context to be used in the SSL connection

AT+CCHSSLCFG=0,0

OK

//connect to SSL/TLS server

AT+CCHOPEN=0, "www.baidu.com", 443,2

OK

+CCHOPEN: 0,0

//send data to server

AT+CCHSEND=0,121

>GET / HTTP/1.1

Host: www.baidu.com

User-Agent: MAUI htp User Agent

Proxy-Connection: keep-alive

Content-Length: 0

OK

+CCHSEND: 0,0

//report the received data from server

+CCHRECV: DATA,0,917
HTTP/1.1 200 OK
Accept-Ranges: bytes
Cache-Control: no-cache
Connection: Keep-Alive
Content-Length: 227
Content-Type: text/html
Date: Tue, 04 Sep 2018 06:21:35 GMT
Etag: "5b7b7f40-e3"
Last-Modified: Tue, 21 Aug 2018 02:56:00 GMT
P3p: CP=" OTI DSP COR IVA OUR IND COM "
Pragma: no-cache
Server: BWS/1.1
Set-Cookie: BD_NOT_HTTPS=1; path=/; Max-Age=300
Set-Cookie: BIDUPSID=D95046B2B3D5455BF01A622DB8DED9EA; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com
Set-Cookie: PSTM=1536042095; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com
Strict-Transport-Security: max-age=0
X-Ua-Compatible: IE=Edge,chrome=1

```
<html>
<head>
    <script>
        location.replace(location.href.replace("https://","http://"));
    </script>
</head>
<body>
    <noscript><meta http-equiv="refresh" content="0;url=http://www.baidu.com/"></noscript>
</body>
</html>
```

//Disconnect from the Service

AT+CCHCLOSE=0

OK

+CCHCLOSE: 0

//stop SSL Service

AT+CCHSTOP

OK

+CCHSTOP: 0

3.6 Access to SSL/TLS server in transparent mode

Following commands shows how to access to a SSL/TLS server with not verifying the server in transparent mode.
It needs to configure the sending and receiving mode to 1(the transparent mode).
Only the session 0 is support the transparent mode.

```
// Set the transparent mode
AT+CCHMODE=1
OK

// Enable reporting +CHSEND result
AT+CCHSET=1
OK

// start SSL service, activate PDP context
AT+CCHSTART
OK

+CCHSTART: 0
// Set the first SSL context to be used in the SSL connection
AT+CCHSSLCFG=0,0
OK

//connect to SSL/TLS server
AT+CCHOPEN=0, "www.baidu.com", 443,2
CONNECT 115200
//send data to server
GET / HTTP/1.1
Host: www.baidu.com
User-Agent: MAUI htp User Agent
Proxy-Connection: keep-alive
Content-Length: 0

//report the received data from server
HTTP/1.1 200 OK
Accept-Ranges: bytes
Cache-Control: no-cache
Connection: Keep-Alive
Content-Length: 227
Content-Type: text/html
Date: Tue, 04 Sep 2018 06:26:03 GMT
Etag: "5b7b7f40-e3"
```

Last-Modified: Tue, 21 Aug 2018 02:56:00 GMT
P3p: CP=" OTI DSP COR IVA OUR IND COM "
Pragma: no-cache
Server: BWS/1.1
Set-Cookie: BD_NOT_HTTPS=1; path=/; Max-Age=300
Set-Cookie: BIDUPSID=F19D0F1E532ED84CE275BC1006F91F9E; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com
Set-Cookie: PSTM=1536042363; expires=Thu, 31-Dec-37 23:55:55 GMT; max-age=2147483647; path=/; domain=.baidu.com
Strict-Transport-Security: max-age=0
X-UA-Compatible: IE=Edge,chrome=1

```
<html>
<head>
    <script>
        location.replace(location.href.replace("https://","http://"));
    </script>
</head>
<body>
    <noscript><meta http-equiv="refresh" content="0;url=http://www.baidu.com/"></noscript>
</body>
</html>
```

//switch to command mode
+++
OK
//Disconnect from the Service
AT+CCHCLOSE=0
OK

CLOSED
//stop SSL Service
AT+CCHSTOP
OK

+CCHSTOP: 0

3.7 Download certificate into module

Following commands shows how to download certificate into module.

```
// download file with ASCII coding file name  
AT+CCERTDOWN="client_key.der",1702  
> -----BEGIN RSA PRIVATE KEY-----  
MIIEowIBAAKCAQEAlwuz/TNa+foGBG6rXpWE1Wnuc+GN9vS7MRenKOH+z2UfGuaV  
BSb8VYFCgoL4RnWLwXAcLlaqw88zlCN89EK6IydaAwNmI/U6nu3oPsVkn8r9+sOX  
yh9VD01DmSU349QWJvRgt1ocsFI1VTdd6RDkVtu7FdKv4XC5WHcOD7yrEIsVa7+G  
Qbnm5cCCz8E75HH8vHZAOFeaV3HvIHnh/1RZ+jh4ysyhEmFNOFCn3r9v2yu4kPRX  
43xEsB13Ue4HgSbnT+Q7LIEK+dfsmUBoSpsS2NAmQOiqGrmmYygT3/V/ISX54hit  
gli5bvg9DuNHYBwh2C+4nyZF95pMj2dEJf4jNwIDAQABoIBAAJ9ze06QKD079p4  
3NjFjJhck/NTYB0XslK/+iDhgWt4VogCD6kzGGxsomU2tdOrsq9xIvXcthpeu5IQ  
98mrpBhaWNC96JxlOh9O+0q1xNAh8AiH22QZGjUTaC8Jfx+B6w+fbkz37os1/+00  
6ZajkbChFTfp7r7ANj5wUEoQKZ4vNpLJxLWDk6uH4ZMNveWcBaZQ21TUg9ZmoskK  
EJ2ZE/3kOSBgi2B6F50zyL8f1mbqPahHNLqtrndV5/Lr4n74TqZXRwt5Cl9GrBv  
tYXDHe+5Y7e1TUIXV00AMDIk+3cVR8m8Oa20tSdXjcw2iUk9brxb4uxreOouGfPW  
5IO+q1ECgYEAA4Kkok17DVx5FiapFQvJ2Jqi2/WhzDncuBGbZtcLZnwRVfkPn3cBZ  
JGNwxYyfEdwItPvTYQYh6Qg81XRdSRfF43GzkQXNmkPOdZM0x3tFwzV6K5Fg7aeR  
g50UddaA9MraCltOgK++7C6BvA3ImXciK4VWeSZOmDW99Y6mgf92RdkCgYEArB2u  
/Id72LGQBmx0Z+36Hf1dxo6RQ+dB+m6XBMR8iuB/jGO/5PHdFoKoF2qa9Yj2W1+X  
B29Xmc1HS6GTvkDIIsN5JXNO7fDmlAxd5whbwDdcmv3VEt8xJ2UeACIawjKtVcFoH  
LRNlvDBttWVvlCZg+9HfVpuPm14oFxN/HtSXt48CgYACxDJ6thUDspy6mD0oGOI5  
kaRHNI0OJYuMhFOz+EVDrvLqfh2RzneKiuruU8/1oVb+G4e7zx6FxxMwsbEgYEmQ  
hmrmo0Kn3qPhMMHanvr572Oku7KM2p5hF4MT/GM0IHdU31D1JrTcJap1TVomAaCL  
FqY88arQFwFSz8Hfle0r6QKBgCbQLtTdzKzqJdt8+6cwQFYg+9O59MJGVVeefNsdp  
chhzVfAX0n9Tl5Lq9fMJ5FX4g+3JGargjfWuGCTTFBk0TM2t4wde7AmwiivU5LU  
T2Af06pLTKrSE9k+yX2iug+O156VfsbIeAm/Ng5RCJ91JCvFgULro6/axNmWORf  
9rK7AoGBAIK4edrX1MjerCsLu3y9Dy4pAx6ER6ei4xpkO25U8wUcqqc+YD2m2xlA  
DjqROITeaxXkmPlRKAXVarhk8LmXT/oDFUAPsTqUZ9LBriqtMi+G2OFPbdKDwe  
ZBNAGwFpFIUVoi0UYnZF8rBq0tepqvivrayEWdKKfMMJjq+l72SxD
```

-----END RSA PRIVATE KEY-----

OK

// download file with not ASCII coding file name

AT+CCERTDOWN={non-ascii}"262378344532443B262378353334453B2E70656D",1918

>-----BEGIN CERTIFICATE-----

MIIFRDCCAYygAwIBAgIIZmPau7FelQswDQYJKoZIhvcNAQELBQAwQDELMakGA1UE
BhMCU0kxGzAZBgNVBAoMEnN0YXRILWluc3RpdHV0aW9uczEUMBIGA1UEAwLVGF4
IENBIFRlc3QwHhcNMTUwNzIzMUYOTA1WhcNMzUwNzIzMUYOTA1WjBAMQswCQYD
VQQGEwJTSTEbMBkGA1UECgwSc3RhdGUtaW5zdGl0dXRpb25zMRQwEgYDVQQDDAtU
YXggQ0EgVGVzdDCCAiIwDQYJKoZIhvcNAQEBBQADggIPADCCAg0CggIBALmH3XNA
KDgN8+G2jX4W/a7LTER10VbRhkGeuc9zyOuj9gigYXLno4Im/S4iXMcCs1IxgSsj
NJ1YMOje4qgHbFKQwWV588VDw7/fiMMZIXvFjHfladdHASEDMT53bKX3HIdJZ/iL
6xhpJ/+C/I8dnWcMZUkeP+9BUAni/I2xrHaAVlli0aS6uc/DjO7b4Gj1Vl4FGIHo
DIH+LmWz26P2gg2xnpWgIxXzs5sN8nYErwu+6h/9xREHco8PPCAZb5HZhqolYzk
N1S1Do6qAzt/wJM0mhWOWHt9fhp/RoYQ5ZFCIZmgd1cJcr6S6U7ebAQ+yYRsIWU5
+FLYZ4Zlt3ZAHNWyraMee/kFsaGcO21cwE+tPDOIn41B8XvfaXApQt4+TejZWzoH
V0ojA+9H8V+wCFVMJssViFOzuS6SIEZ/xzslo+B//cfUkq/PnWLJHEy4BJXsj4+F
CvliZ7Lq3B/RcQmBjmTRQ0mxahiMGrrQW4TLjUYgY8IfwKfMfwFwVwUyk5br9Grs
UX7jy7+Xx17Qed4p0jjOC7KutzRIGr6ULSk11qpd5IHeIwzSOaTXk6rAzZYupPH5
KvY65mdRfq0C0cB2bMvk9m9lyeLfZz5+L9XDLlodTdwOeWaKvjFErT8WSEkpHxtG
q13TVgicoxsHC2K+8hpFjpaz69ZCmTzj4/17AgMBAAGjQjBAMB0GA1UdDgQWBHQz
zVr7CUfHAeY2KCb1gXy3jjX3sjAPBgNVHRMBAf8EBTADAQH/MA4GA1UdDwEB/wQE
AwIBBjANBqkqhkiG9w0BAQsFAAACAgEAR9xtbaNa/jSAAyqe3aq88GG7rCyxROGH
BPcakfMmhx1cLYdcY5ATXL/n67eo+S+1g7e/sK3fVXav5qWs9oUEhAOgcOACMohu
JlBbMq2Qp8ldpiRWCCyiY1vGQcHcZ02oey/c06fBZE4iqJdYAhYhsBB5H+idtwJ
s6Lade4wqG58hWCNKBXU+KWDckGGX5CxsfU7gdYgjyKq0ow60qQWi4H8pD+WO1Bn
rvISkAT7vMk2BOz+YICKZmuq0h3PCkK5T6xA01fUZCaeze0RozFaekDBEHK0bc1D
My3SKbB3cjdcMzmV8sVdxnNOTxlrP7+BinctxT3q3Va96kTmwI5pD0x6KOwC7Urr

53ubhI3U2XBAzkk14IDLU+7tqBqhDWwIMN0NyW1MRTF8JB9Rz+4yCcDWMOT/FZg7

C60RrcnaO/0GETDz6XI6zedBXo1Q/rJTtXMOr8iVnc+joZyO2ImOuTwP3C7M3Bnp

gFHqDtD48n9PV9prhbD4fYPyMe/3rshtBcpGAy2cGjpsP28pkvP8lwBaP8pnpxvQ

7d3oiCBzznaOHjhm8+8C53b/1txzj/LP/4ZzIynsOhxy4cihEPhAg1MKUY9qnbw9

9Q6EKrCSqk3TPqiWrTtu4pxyiEiquCHk8n+HX5cVhxUkaEShdx4bjgvKB7JRF2T2

ST1lrKEM2DY=

-----END CERTIFICATE-----

OK

//list certificate files

AT+CCERTLIST

+CCERTLIST: "中华.pem"

+CCERTLIST: "client_key.der"

OK