

- Operating voltage: 4V~18V
- Low standby current
- Low power and high noise immunity CMOS technology
- 3⁹ different codes

- Minimum of two transmission words
- Built-in oscillator needs only 5% resistor
- Interface with RF or infrared transmission medium
- Minimal external components

- Burglar alarm system
- Smoke and fire alarm system
- Garage door controllers
- Car alarm system

- Security system
- Cordless telephones
- Other remote control systems


The HT6026 is a CMOS LSI encoder designed for remote control system applications. It is capable of encoding 9 bits of information which consists of N address bits and 9-N data bits. Each address/data input is externally trinary programmable by external switches. The programmable

address/data is transmitted along with the header bits via an RF or an infrared transmission medium upon receipt of a trigger signal ($\overline{\text{TE}}$).

**HT6026
-16 DIP/NSOP**

The block diagram illustrates the 9-channel data acquisition system. It features an Oscillator block that receives OSC1 and provides OSC2 and OSC3 signals. The OSC2 signal is divided by 4 (÷4 Divider) and then used by a ÷9 Counter & 1 of 9 Decoders. The counter also receives a TE (Timing Enable) signal. The output of the counter is connected to a Transmission Gate Circuits block, which also receives AD0 and AD8 signals. The Transmission Gate Circuits block outputs to a Trinary Detector. The Trinary Detector's output is connected to a Sync. Circuit, which then feeds into the Data Select & Buffer. The Data Select & Buffer also receives the ÷4 Divider's output and produces the DOUT signal. Power supply connections for VDD and VSS are shown at the bottom. A dashed line encloses the main processing blocks (Oscillator, ÷4 Divider, ÷9 Counter & 1 of 9 Decoders, Transmission Gate Circuits, Trinary Detector, Sync. Circuit, and Data Select & Buffer).

Pad Coordinates

Unit: μm



Pad No.	X	Y	Pad No.	X	Y
1	-598.00	689.00	9	160.00	-687.00
2	-674.00	433.00	10	670.00	-687.00
3	-674.00	126.00	11	670.00	-347.00
4	-674.00	-162.00	12	670.00	172.00
5	-674.00	-449.00	13	670.50	689.50
6	-598.00	-687.00	14	270.00	689.00
7	-342.00	-687.00	15	-84.00	689.00
8	-127.00	-687.00	16	-299.00	689.00

Chip size: $1650 \times 1680 (\mu\text{m})^2$

* The IC substrate should be connected to VSS in the PCB layout artwork.

Pin Description

Pin No.	Pin Name	I/O	Internal Connection	Description
1~7	AD0~AD6	I	TRANSMISSION GATE	Input pins for address/data AD0~AD6 setting. They can be externally set to VDD, VSS, or left open.
8	VSS	I	—	Negative power supply (GND)
9~10	AD7~AD8	I	TRANSMISSION GATE	Input pins for address/data AD7~AD8 setting. They can be externally set to VDD, VSS, or left open.
11	OSC1	I	OSCILLATOR	Oscillator input pin
12	OSC2	O	OSCILLATOR	Oscillator output pin
13	OSC3	O	OSCILLATOR	Oscillator output pin
14	$\overline{\text{TE}}$	I	CMOS IN Pull-high	Transmission enable, active low
15	DOUT	O	CMOS OUT	Encoder data serial transmission output
16	VDD		—	Positive power supply

Approximate internal connection circuits

Absolute Maximum Ratings

Supply Voltage.....	-0.3V to 24V	Storage Temperature	-50°C to 125°C
Input Voltage	$V_{SS}-0.3$ to $V_{DD}+0.3V$	Operating Temperature	-20°C to 75°C

Note: These are stress ratings only. Stresses exceeding the range specified under "Absolute Maximum Ratings" may cause substantial damage to the device. Functional operation of this device at other conditions beyond those listed in the specification is not implied and prolonged exposure to extreme conditions may affect device reliability.


Electrical Characteristics
 $T_a=25^{\circ}C$

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit
		V_{DD}	Conditions				
V_{DD}	Operating Voltage	—	—	4	—	18	V
I_{STB}	Standby Current	5V	Oscillator stops	—	0.1	0.3	μA
		15V		—	0.1	0.5	μA
I_{DD}	Operating Current	5V	No load, $f_{OSC}=18kHz$	—	500	900	μA
		15V	No load, $f_{OSC}=22kHz$	—	2000	3000	μA
I_{DOUT}	Output Drive Current	5V	$V_{OH}=0.9V_{DD}$ (Source)	-1.0	-1.7	—	mA
		15V		-8.0	-14.0	—	mA
		5V	$V_{OL}=0.1V_{DD}$ (Sink)	0.8	1.5	—	mA
		15V		5.0	10.0	—	mA
V_{IH}	"H" Input Voltage	—	—	$0.7V_{DD}$	—	V_{DD}	V
V_{IL}	"L" Input Voltage	—	—	0	—	$0.3V_{DD}$	V
R_{TE}	\overline{TE} Pull-high Resistance	5V	$V_{TE}=0V$	—	800	—	k Ω
		15V		—	250	—	k Ω
f_{OSC}	Oscillator Frequency	5V	$R_{EXT}=10k\Omega$ $C_{EXT}=2000PF$	—	18	—	kHz
		15V	$R_S=20k\Omega$	—	22	—	kHz

Functional Description


Operation

The HT6026 encoder begins a one-word transmission cycle upon receipt of a transmission enable (\overline{TE} , active low). This cycle will repeat itself as long as the transmission enable (\overline{TE}) is held low. Once the transmission enable returns high, the encoder output completes its final $N \times 2$ word cycle, and then stops as shown in the Transmission timing diagram below. The total number of transmission cycles allowed is always automatically adjusted to an even number.




Information word

An information word consists of two periods as shown:



Address/data waveform

Each programmable address/data pin can be externally set to one of the following three logic states:




Address/data programming (preset)

The status of each address/data pin can be individually preset to logic "high", "low", or "floating". If a transmission enable signal is applied, the encoder scans and transmits the status of the 9-bit address/data serially in the order AD0 to AD8. But if the trigger signal is not applied, the chip only consumes a standby current which is less than 1 μ A (for VDD=5V).

The address pins are usually preset to transmit data codes with their own particular security codes by the DIP switches or PCB wiring, while the data is selected using push buttons or electronic switches.

The following figure demonstrates an application using the HT6026:



The transmitted information is as listed:


Pilot & Sync.	AD0	AD1	AD2	AD3	AD4	AD5	AD6	AD7	AD8
	1	Z	1	Z	Z	Z	0	1	Z

Z: floating


Transmission enable

Transmission is enabled by applying a low signal to the \overline{TE} pin. The HT6026 is enabled and outputs address/data codes from the DOUT pin when \overline{TE} is set to "low" for more than 65ns.


Flowchart



Oscillator frequency vs supply voltage



Application Circuit



Holtek Semiconductor Inc. (Headquarters)

No.3, Creation Rd. II, Science Park, Hsinchu, Taiwan
Tel: 886-3-563-1999
Fax: 886-3-563-1189
<http://www.holtek.com.tw>

Holtek Semiconductor Inc. (Taipei Sales Office)

4F-2, No. 3-2, YuanQu St., Nankang Software Park, Taipei 115, Taiwan
Tel: 886-2-2655-7070
Fax: 886-2-2655-7373
Fax: 886-2-2655-7383 (International sales hotline)

Holtek Semiconductor Inc. (Shanghai Sales Office)

7th Floor, Building 2, No.889, Yi Shan Rd., Shanghai, China 200233
Tel: 021-6485-5560
Fax: 021-6485-0313
<http://www.holtek.com.cn>

Holtek Semiconductor Inc. (Shenzhen Sales Office)

43F, SEG Plaza, Shen Nan Zhong Road, Shenzhen, China 518031
Tel: 0755-8346-5589
Fax: 0755-8346-5590
ISDN: 0755-8346-5591

Holtek Semiconductor Inc. (Beijing Sales Office)

Suite 1721, Jinyu Tower, A129 West Xuan Wu Men Street, Xicheng District, Beijing, China 100031
Tel: 010-6641-0030, 6641-7751, 6641-7752
Fax: 010-6641-0125

Holmate Semiconductor, Inc. (North America Sales Office)

46712 Fremont Blvd., Fremont, CA 94538
Tel: 510-252-9880
Fax: 510-252-9885
<http://www.holmate.com>

Copyright © 1997 by HOLTEK SEMICONDUCTOR INC.

The information appearing in this Data Sheet is believed to be accurate at the time of publication. However, Holtek assumes no responsibility arising from the use of the specifications described. The applications mentioned herein are used solely for the purpose of illustration and Holtek makes no warranty or representation that such applications will be suitable without further modification, nor recommends the use of its products for application that may present a risk to human life due to malfunction or otherwise. Holtek's products are not authorized for use as critical components in life support devices or systems. Holtek reserves the right to alter its products without prior notification. For the most up-to-date information, please visit our web site at <http://www.holtek.com.tw>.