Copyright 2009 FDT Net- www.fdt.com.tw, E-mail- fdt@fdt.com.tw add: NO. 85, Fuhsing Rd. Sce. 1, South Dist., Taichung City402, Taiwan tel: 886-4-22619577 fax: 886-4-22623978



Start 4-point calibration

Smart Graphic Module

-. Assemble the components according the illustration





二. After install, open "Command Pilot"

Command Filot			X
Send_Receive Source File			
Base Setting ComNumber Com1	ONE LINE (<u>2</u>)	RE-START ()	
BaudRate 115200bps CLOSE	AUTO RUN (c)	PAUSE (p)	HELP
checksum	Command End Retu	rn Code	
Delay ms	Status :	0	
Transmitter Command Description Display	Key Code : L_Key IR Code : L_IR	Edit1	Edit1
	Receiver Comma	and Display	~

CommandPilot

■Setting 「COM port number」: to your PC for GTB 。 ■Setting 「Baud Rate」: Please select "115200bps" 。

0.06.11.0



Ξ. Input two command **F1 07 F8 25 00 01 00 1E F4.&F1 07 F8 25 00 01 01 1F F4.i** in the marking area and then execute the 4 point calibration procedure ∘

Command Pilo	t					X
Send <u>Receive</u>	Source File					
Base Setting ComNumber	Com1 💌		ONE LINE (<u>z</u>)	RE-START (j)		
BraudRate 1	15200bps 💌	CLOSE	AUTO RUN (<u>c</u>)	PAUSE (<u>p</u>)	HELP	
F1 07 F8 25 00	01 01 1月F4	checksu	Command End F	Return C		
	Delay	ms	Status :	0		
Transmitter Con F1 07 F8 25 00 0 F1 07 F8 25 00 0	nmand Description Dis 1 00 1E F4 1 01 1F F4	play	Key CodeL_Key IR Code :L_IR	Edit1	Edit1	
			Receiver Comma	and Display	~	



0.06.11.0