



LEDTECH ELECTRONICS CORP.

NANYA ROAD,MUGANG ZHAOQING
CITY GUANGDONG CHINA.

TEL:86-758-2875541,2870651,2877464,2876185,2877017

FAX:86-758-2878014

Http://www.ledtech.com.tw

SPECIFICATION

PART NO. : LT8A32-43-UR91-T4

0805 SMD CHIP LED



Approved by

Checked by


Prepared by

Tung

Lian

Show

Package Dimensions



Notes:

1. All dimensions are in mm.
2. Tolerance is ± 0.1 mm unless otherwise noted.

Description

Part No.	LED Chip		Lens Color
	Material	Emitting Color	
LT8A32-43-UR91-T4	AlGaInP/GaAs	Yellow	White Diffused

Absolute Maximum Ratings at Ta=25 °C

Parameter	Symbol	Rating	Unit
Power Dissipation	P _D	72	mW
Reverse Voltage	V _R	5	V
D.C. Forward Current	I _f	30	mA
Peak Current(1/10Duty Cycle,0.1ms Pulse Width.)	I _f (Peak)	80	mA
Operating Temperature Range	T _{opr.}	-30 to +80	°C
Storage Temperature Range	T _{stg.}	-40 to +85	°C
Soldering Temperature.	T _{sol.}	Reflow Soldering:260°C for 10 sec.	

Electrical and Optical Characteristics:

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Luminous Intensity	I _v	I _f =20mA	24.4	50		mcd
Forward Voltage	V _f	I _f =20mA	1.8		2.4	V
Peak Wavelength	λ _p	I _f =20mA		591		nm
Dominant Wavelength	λ _d	I _f =20mA		589		nm
Reverse Current	I _r	V _R =5V			100	μA
Viewing Angle	2 θ 1/2	I _f =20mA		140		deg
Spectrum Line Halfwidth	Δλ	I _f =20mA		15		nm

Notes:1.The datas tested by IS tester.

2. Customer's special requirements are also welcome.

Product Specification

	Specification	Material	Quantity
Iv	Q:24.4-36.7 R: 36.7-51.6mcd S: 51.6-75.6mcd @20mA		
λd	36: 584-588 nm 37: 588-592 nm 38: 592-596 nm @20mA		
Vf	G: 1.8-2.0v H: 2.0-2.2v J: 2.2-2.4v @20mA		
Ir	<100 μ A @Vr=5V		
Resin	White Diffused	Epoxy resin	
Carrier tape		Conductive black tape	4000pcs per reel
Reel		White	
Label	LT standard	Paper	
Packing bag	250x220mm	Aluminum laminated bag	One reel one bag
Carton	LT standard	Paper	Non-specified
Others:			

Lot No.:


W O Z A 3 0 0 0 6 2
 ↑ ↑ ↑
 Internal Tracing Code Mfg. Year Flowing Code

BIN CODE :


X X - X
 ↑ ↑ ↑
 IV Rank VF Rank λd Rank

Typical Electrical/Optical Characteristic Curves


(25°C Ambient Temperature Unless Otherwise Noted)




FORWARD CURRENT VS. APPLIED VOLTAGE




RELATIVE INTENSITY VS. FORWARD CURRENT




FORWARD CURRENT VS. AMBIENT TEMPERATURE



RELATIVE INTENSITY VS. AMBIENT TEMPERATURE



RELATIVE INTENSITY VS. WAVELENGTH



Radiation Diagram

Precautions in Use:

Storage

Recommend storage environment

Temperature : $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$ ($41^{\circ}\text{F} \sim 86^{\circ}\text{F}$)

Humidity : 60% RH Max.

Use within 7 days after opening of sealed vapor/ESD barrier bags.

If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions. Baking treatment : $60 \pm 5^{\circ}\text{C}$ for 24 hours.

Fold the opened bag firmly and keep in dry environment.

Soldering

Reflow Soldering

Recommend use of upper and lower heater type reflow furnace.

260°C Max for up to 10 seconds, one time only.

Pre-heat is 150°C Max for up to 2 minutes Max.

In case of screen-printing, keep metal mask thickness between 0.2mm and 0.3mm.

Cleaning

Surface condition of this device may change when organic solvents such as trichloroethylene or acetone were applied.

Avoid using organic solvent.


Recommend ultrasonic method 300W Max.

Packaging


EIA-481A standard package.

In 8mm tape on 4000 pcs diameter reels sealed in vapor/ESD barrier bags.


Reflow Temp/Time:




Reflow Soldering Pad Dimensions



Dimensions for Tape



Dimensions for Reel




Notes:

- 1.All dimensions are in mm, tolerance is ± 2.0 mm unless otherwise noted.
- 2.Specifications are subject to change without notice.


Dimensions for Tape

Reel : 4,000PCS



PART NO	XXXXXX
LOT NO	XXXXXX
QUANTITY	XXXXXX
DATE	XXXXXX
BIN CODE	XXXXXX


Bag : 4,000PCS



溼氣敏感材料
MOISTURE SENSITIVE DEVICES
1. 在5°C~30°C密封貯藏，2年有效。
Shelf life in sealed bag : 24 months
at 5°C~30°C .
2. 開封後需在168小時內使用。
Devices have to be mounted within
168 hours after this bag is opened .


PART NO	XXXXXX
LOT NO	XXXXXX
QUANTITY	XXXXXX
DATE	XXXXXX
BIN CODE	XXXXXX

5 Bags : 20,000PCS



PART NO	XXXXXX
LOT NO	XXXXXX
BIN CODE	XXXXXX
QUANTITY	XXXXXX
DATE	XXXXXX

8 Boxes : 160,000PCS



C/T NO	XX
PART NO	XXXXXX
QUANTITY	PCS
N. W.	KGS
G. W.	KGS
REMARK	

Notes:

- 1.7 inch reel-4000 pieces per reel.
- Minimum packing quantity is 500 pieces for remainders.
- The maximum number of consecutive missing lamps is two.