






SCHMATIC



PCB LAYOUT

RoHS Compliance

5	CONTACT	BRASS	2	Ag PLATED	6	SPRING	STEEL WIRE	2	
3	TERMINAL	BRASS	6	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1	NATURAL
1	FRAME	S P C C	1	Ni PLATED	2	KNOB	P O M	1	G 1.5-15
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED	SPECIFICATION	TITLE: SLIDE SWITCH (1P2T)	
	RATING: DC 30V 0.3A	MODEL NO: SS-12F02(G)	
	CONTACT RESISTANCE: 30mΩ max.	TOLERANCE	UNIT: MM
	INSULATION RESISTANCE: 500MΩ at 500V DC	UP TO 1.0:±0.1	SCALE: 2:1
	WITHSTAND VOLTAGE: AC 500V for 1 minute	1.0 TO 10.0:±0.2	VERSION: 01
	OPERATION FORCE: REFER ATTACH SPECIFICATION	OVER 10.0:±0.3	DRWG NO:
SWITCHING LIFE: 10K cycles min.			
BY: 	SEE-PLUS INDUSTRIAL LTD.		 
DATE: 03-JAN-2000			