



SCHEMATIC



PCB LAYOUT



RoHS
Compliance

MODEL NO.	H	MODEL NO.	H
TC-00104-00	4.30	TC-00104E-00	7.00
TC-00104A-00	5.00	TC-00104F-00	8.00
TC-00104B-00	7.30	TC-00104G-00	12.50
TC-00104C-00	9.50	TC-00104H-00	13.50
TC-00104D-00	13.00	TC-00104L-00	6.00

5	CONTACT	P B S	1	Ag PLATED
3	TERMINAL	BRASS	4	Ag PLATED
1	FRAME	NYLON	1	
NO	PART	MATERIAL	QTY	REMARKS

4	COVER BOARD	SPCC	1	Ni PLATED
2	KNOB	NYLON	1	
NO	PART	MATERIAL	QTY	REMARKS

ISSUED		SPECIFICATION		TITLE: TACT SWITCH			
	RATING: DC 12V 50mA		MODEL NO: TC-00104 ()-00-M				
	CONTACT RESISTANCE: 100mΩ Max.						
	INSULATION RESISTANCE: 100MΩ at 500V DC		TOLERANCE		UNIT: MM	DWN.	
	WITHSTAND VOLTAGE: AC 250V for 1 minute.		UP TO 1.0:±0.1		SCALE: 4:1	CHK'D.	
	OPERATION FORCE: REFER ATTACH SPECIFICATION		1.0 TO 10.0:±0.2		VERSION: 03		
SWITCHING LIFE: 100k Cycles Min.		OVER 10.0:±0.3		DRWG NO:	APPD.		
BY: 		SEE-PLUS INDUSTRIAL LTD.					
DATE: 07-NOV-2006							